

Material:

- The steel meets or exceeds the physical properties of ASTM A1011 GR 33, except with SS, ST & AL finishes.

Finishes:

- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Hot Dip Galvanized (HD):** Conforms to ASTM A123 or A153
- **Perma-Gold (GD):** Conforms to ASTM B633, Type II SC1
- **Stainless Steel, Type 304 (SS4):** ASTM A240, Type 304 *
- **Stainless Steel, Type 316 (SS6):** ASTM A240, Type 316 *
- **Aluminum (AL):** TBD

Part No.	Conduit Size	O.D. Size	Ga. (Thickness)	Finish	Product Weight / Piece (lbs)
EMT-A-1"	1" (25)	1.163" (29.5)	14 (1.9)	EG	0.15
EMT-A-1"	1" (25)	1.163" (29.5)	14 (1.9)	HD	0.16
EMT-A-1"	1" (25)	1.163" (29.5)	14 (1.9)	SS4	0.15
EMT-A-1"	1" (25)	1.163" (29.5)	14 (1.9)	AL	0.05
EMT-A-1/2"	1/2" (13)	0.706" (17.9)	16 (1.5)	EG	0.11
EMT-A-1/2"	1/2" (13)	0.706" (17.9)	16 (1.5)	HD	0.22
EMT-A-1/2"	1/2" (13)	0.706" (17.9)	16 (1.5)	SS4	0.11
EMT-A-1/2"	1/2" (13)	0.706" (17.9)	16 (1.5)	AL	0.037
EMT-A-1-1/2"	1-1/2" (38)	1.740" (44.2)	12 (2.7)	EG	0.29
EMT-A-1-1/2"	1-1/2" (38)	1.740" (44.2)	12 (2.7)	GD	0.29
EMT-A-1-1/2"	1-1/2" (38)	1.740" (44.2)	12 (2.7)	SS4	0.29
EMT-A-1-1/4"	1-1/4" (32)	1.510" (38.4)	14 (1.9)	EG	0.18
EMT-A-1-1/4"	1-1/4" (32)	1.510" (38.4)	14 (1.9)	SS4	0.18
EMT-A-1-1/4"	1-1/4" (32)	1.510" (38.4)	14 (1.9)	AL	0.06
EMT-A-2"	2" (51)	2.197" (55.8)	12 (2.7)	EG	0.33
EMT-A-2"	2" (51)	2.197" (55.8)	12 (2.7)	HD	0.35
EMT-A-2"	2" (51)	2.197" (55.8)	12 (2.7)	SS4	0.33
EMT-A-2"	2" (51)	2.197" (55.8)	12 (2.7)	AL	0.11
EMT-A-3/4"	3/4" (19)	0.922" (23.4)	16 (1.5)	EG	0.12
EMT-A-3/4"	3/4" (19)	0.922" (23.4)	16 (1.5)	HD	0.13
EMT-A-3/4"	3/4" (19)	0.922" (23.4)	16 (1.5)	SS4	0.12
EMT-A-3/4"	3/4" (19)	0.922" (23.4)	16 (1.5)	AL	0.04
EMT-A-3/8"	3/8" (10)	0.577" (14.7)	16 (1.5)	EG	0.09
EMT-A-3/8"	3/8" (10)	0.577" (14.7)	16 (1.5)	SS4	0.09

